

USB2.0 Hub intern 4 Port 3,5" / 5,25"



Features

- Compliant with USB2.0 specification
- Compliant with UHCI and OHCI specification
- Supports high-speed (480 Mbps), full-speed (12 Mbps) and low-speed (1.5 Mbps)
- Plug & Play
- Hot Swappable
- Over current protection for each port
- Chains up to 127 USB devices
- Fits into 3.5" and 5.25" slots
- Supports Windows 98SE / ME / 2000 / XP

Package Contents

- 1x USB2.0 Hub intern 4 Port 3,5" / 5,25"
- 1x USB2.0 cable A/M > Mini5p/M, 1m
- 1x Y-type power cable, 0.2m
- 1x Set of screws
- 1x User manual

Specification

Interface standard	USB V2.0
Connectors	4x USB Type A/F downstream 1x USB Mini 5Pin/F upstream 1x Power 4Pin
Data transfer rate	480 Mbps, 12 Mbps, 1,5 Mbps
Chipset	Genesys GL850
Power mode	Self Power Mode
Cable	USB2.0 Cable A/M > Mini 5P/M, 1m
Enclosure	Plastic
Operating temperature	5° - 40° C
Storage temperature	-20° - 40° C
Relative humidity	0 - 80% , non condensing
Dimensions (W x H x D)	100/148 x 25/43 x 92/139 mm
Weight	0.133 kg
Dimensions (packing box)	200 x 50 x 165 mm
Overall weight	0.298 kg

