



Network Management Card

38200107

The Equip 38200107 is a web-based Network Management Card (NMC) for monitoring UPS via SNMP protocol.

Key Features

Current support feature
 nonsupport
 Support in the future

1、Network Protocol Supported;

Protocol	38200107
BOOTP/DHCP	■
HTTP	■
HTTPS	■
SNMPv1	■
SNMPv3	■
CLI	■
SSL	■
SSH	■
SMTP	■
NTP	■
(T)FTP	■
IPv6	■

2、Functions supplied:

A、SNMP

Function	38200107
SNMPv3	<input checked="" type="checkbox"/>
MIB support	RFC1628 MIB PPC MIB
TRAP	<input checked="" type="checkbox"/>

B、Function with UPS

Function		38200107
UPS Monitor	UPS Status	Static chat
UPS Control	Remote Start/Turn off UPS	<input checked="" type="checkbox"/>
	Weekly Schedule	<input checked="" type="checkbox"/>
	Special Day Schedule	<input checked="" type="checkbox"/>
	Battery Test	<input checked="" type="checkbox"/>
	Battery Test Schedule	<input checked="" type="checkbox"/>
LOG	Log	UPS data log UPS event log NMC System event log
Environment	Temperature & Humidity	<input checked="" type="checkbox"/>

Parameters showed by the card:

Parameters	38200107
Input Voltage	<input checked="" type="checkbox"/>
Input Current	<input checked="" type="checkbox"/>
Input Frequency	<input checked="" type="checkbox"/>
Output Voltage	<input checked="" type="checkbox"/>
Output Current	<input checked="" type="checkbox"/>
Output Frequency	<input checked="" type="checkbox"/>
Rating Voltage	<input checked="" type="checkbox"/>
Rating Current	<input checked="" type="checkbox"/>
Rating Power	<input checked="" type="checkbox"/>
Apparent Power	<input checked="" type="checkbox"/>
Active Power	<input checked="" type="checkbox"/>
Battery Voltage	<input checked="" type="checkbox"/>
Battery Voltage Per cell	<input checked="" type="checkbox"/>
Battery Cell Number	<input checked="" type="checkbox"/>
Battery capacity	<input checked="" type="checkbox"/>
Battery backup time	<input checked="" type="checkbox"/>
UPS Model Name	<input checked="" type="checkbox"/>
UPS Modules	<input checked="" type="checkbox"/>
Charger Modules	<input checked="" type="checkbox"/>

C、Other function

Function	38200107
Email	4 receivers
Upgrade via network	<input checked="" type="checkbox"/>
Wake On Lan	<input checked="" type="checkbox"/>
RTC	IP support Via network
Switch Hub Extend	<input type="checkbox"/>
Language Support	Multiple languages
Connections Limitation	5 http,3 through SSL

3、Operating Systems supported by shutdown modules

OS	38200107
Windows	
Windows 2000	<input type="checkbox"/>
Server 2003	<input checked="" type="checkbox"/>
Windows XP	<input checked="" type="checkbox"/>
Vista	<input checked="" type="checkbox"/>
Server 2008	<input checked="" type="checkbox"/>
Windows 7	<input checked="" type="checkbox"/>
Linux/UNIX/Mac OS	
Redhat	<input checked="" type="checkbox"/>
Fedora	<input checked="" type="checkbox"/>
Solaris	<input checked="" type="checkbox"/>
Novell SUSE	<input checked="" type="checkbox"/>
FreeBSD	<input checked="" type="checkbox"/>
IBM AIX	<input checked="" type="checkbox"/>
Mac OS	<input checked="" type="checkbox"/>
VMware ESX	<input checked="" type="checkbox"/>
VMware ESXi	<input checked="" type="checkbox"/>